

General Purpose, Single Phase

(NEMA Service Factor), DripProof



Features:

- Heavy gauge steel constructions
- Ball bearings (except as noted)
- Economical split phase or capacitor start designs, as noted
- Service Factor, as noted
- UL Recognized and CSA Certified

Rigid Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/6	1800	115	48	AUTO	4349	5KH39QN9537X	★			\$134	F1	3.9	8.94	3,4,7,20
1/4	1800	115	48	NONE	4354	5KH39QN9538	★			\$137	F1	5.1	8.94	3,4,7,20
	1800	115	48	NONE	H239	5KH33FN6	★			\$184	F1	5.6	8.87	3,7,20
	1800	115	48	AUTO	4362	5KH39QN9686X	★			\$141	F1	5.1	8.94	3,4,7,20
	1800	115/208-230	48	MANUAL	G078	48C17D2034	★			\$189	F1	5.0/2.3-2.5	9.84	2,20
	1800	115/208-230	48	NONE	C147	5KC35JN10	★	G076	48C17D2033	\$175	F1	5.2/2.7-2.6	9.25	2,7,20
	1800	115/208-230	48	AUTO	C148	5KC35JN10X	★			\$237	F1	5.2/2.7-2.6	9.25	2,7,20
	1800	115/230	48	AUTO	C145	5KC35JN8X	★			\$212	F1	5.2/2.6	9.57	2,4,7,20
	1500	110/220	48	NONE	C431	5KC36LN18	★			\$257	F1	5.6/2.8	9.66	2,7,20,50
1/3	3600	115/208-230	48	NONE	G091	48C34D2025				\$151	F1	4.4/2.2-2.2	10.09	2,20
	1800	115/208-230	48	NONE	C153	5KC36LN30	★			\$251	F1	6.0/3.2-3.0	9.66	2,7,20,68
	1800	115/208-230	48	AUTO	C154	5KC36LN30X	★			\$262	F1	6.0/3.2-3.0	9.66	2,7,20,68
	1800	115/208-230	56	NONE	C158	5KC36LN7	★	G093	56C17D2087	\$212	F1	6.0/3.2-3.0	10.32	2,7,20,68
	1800	100-120/200-240	56	NONE	E253	5KCR46JN0085	★			\$306	F1	4.0-3.8/2.0-1.9	10.77	ES,1,20,68
	1800	115/208-230	56	AUTO	C159	5KC36LN7X	★	G094	56C17D2009	\$220	F1	6.0/3.2-3.0	10.32	2,7,20,68
	1800	115/208-230	56	MANUAL	G095	56C17D2010	★			\$226	F1	6.4/3.0-3.2	10.22	2,20
	1200	115/230	56	NONE	G1096	5KC49PN6070	★	G096	56C11D2032	\$316	F1	8.6/4.3	11.48	2,20,68
1/2	3600	115/230	48	NONE	G1098	5KC36JN266	★	G098	48C34D2023	\$168	F1	7.6/3.8	9.66	2,7,19
	3600	115	56	MANUAL	9031	5KC49MN2043Y	★	D014	56C34D2107	\$201	F1	11.5	11.14	2,17
	3600	115/230	56	MANUAL	C1474	5KC37LN502Y	★			\$248	F1	7.4/3.7	10.72	2,17
	3000	110/220	48	NONE	C459	5KC37MN96	★			\$281	F1	7.8/3.9	10.06	2,7,19
	1800	115/230	48	NONE	C164	5KC37NN15	★			\$311	F1	9.2/4.6	10.40	2,7,19
	1800	110-120/200-240	56	NONE	E262	5KCR46MN0092	★			\$359	F1	5.8-5.6/2.9-2.8	10.77	ES,1,19,68
	1800	115/208-230	56	NONE	C167	5KC49GN0010	★	G910	56C17D2011	\$237	F1	8.8/4.2-4.4	10.38	2,19
	1800	115/230	56	AUTO	C168	5KC49GN0010X	★	G911	56C17D2012	\$259	F1	8.8/4.4	10.38	2,19
	1800	115/230	56	MANUAL	C169	5KC49GN0010Y	★	G912	56C17D2013	\$266	F1	8.8/4.4	10.38	2,19
	1200	115/230	56	NONE	C1263	5KC48UN6073	★	G913	56C11D5301	\$405	F1	9.4/4.7	12.76	2,19
3/4	3600	115/208-230	56	NONE	G915	56C34D2100	★			\$218	F1	9.6/4.4-4.8	10.97	2,19
	3600	115	56	MANUAL	9032	5KC49MN2049Y	★	D015	56C34D2094	\$233	F1	12.5	11.14	2,17
	3600	115/230	56	MANUAL	C1475	5KC37NN501Y	★			\$300	F1	10.2/5.1	10.72	2,19
	1800	100-120/200-240	56	NONE	EG271	5KCR49PN0097	★			\$451	F1	9.0-8.8/4.5-4.4	11.37	ES,1,19,68
	1800	115/208-230	56	NONE	C175	5KC46LN0153	★	G917	56B17D2008	\$297	F1	13.2/6.2-6.6	10.78	2,19
	1800	115/230	56	AUTO	C176	5KC46LN0153X	★	G918	56B17D2009	\$342	F1	13.2/6.6	10.78	2,19
	1800	115/208-230	56	MANUAL	G919	56B17D2010	★			\$324	F1	11.0/5.5-5.5	11.47	1,19
	1800	115/208-230	56	MANUAL	C1298	5KC46NN0758Y	★			\$324	F1	11.2/5.8-5.6	10.34	2,19
	1800	115/230	56	MANUAL	C177	5KC46LN0153U	★			\$363	F1	13.2/6.6	10.78	2,19
	1200	115/230	56	NONE	C178	5KCR49WN6075	★	G930	56C11D5302	\$518	F1	12.6/6.3	13.96	ES,1,18
1	3600	115/208-230	56	NONE	C179	5KC38RN60	★	G932	56B34D2030	\$247	F1	12.4/6.4-6.2	11.04	2,19
	3600	115/208-230	56	AUTO	C180	5KC38RN60X	★			\$316	F1	12.4/6.4-6.2	11.04	2,19
	3600	115/230	56	MANUAL	9033	5KC49NN2050Y	★			\$267	F1	16.0/8.0	11.14	d,2,17
	3600	115/208-230	56	MANUAL	D010	56B34D2029	★			\$267	F1	10.6/5.5-5.3	11.72	1,18
	3600	115/230	56	MANUAL	C702	5KC38RN4153Y	★			\$381	F1	12.8/6.5	11.04	2,18
	1800	100-120/200-240	56H	NONE	E280	5KCR48UN0104	★			\$321	F1	11.8-11.4/5.9-5.7	12.66	ES,1,18
	1800	115/208-230	56	NONE	C181	5KC49PN0161	★	G934	56C17D5303	\$321	F1	13.6/6.7-6.8	11.38	2,18
	1800	115/208-230	56	AUTO	C182	5KC49PN0161X	★	G935	56C17D5304	\$341	F1	13.6/6.6-6.8	11.38	2,18
	1800	115/230	56	MANUAL	C1480	5KC49PN0161U	★	G936	56C17D5305	\$353	F1	13.6/6.8	11.38	2,18
	1800	115/208-230	143T	NONE	C188	5KC49PN0162	★	I110	143TCDR5326	\$321	S1	13.6/6.7-6.8	11.77	2,11,18
	1200	115/230	56H	NONE	C183	5KCR49QN6076	★			\$467	F1	12.6/6.3	14.93	ES,1,18
	1200	115/230	182T	NONE	I1141	182TCDW17079		I141	182TCDR17079	\$537	S1	15.0/7.5	15.72	13,18

SINGLE PHASE

Continued on next page.

General Purpose, Single Phase

(NEMA Service Factor), DripProof

Rigid Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1 1/2	3600	115/208-230	56	NONE	G937	56B34D2026	*			\$330	F1	14.8/8.0-7.4	11.72	1,18
	3600	115/230	56	MANUAL	C1477	5KC49PN2144Y	*			\$433	F1	16.8/8.4	11.82	2,18
	3600	115/230	56	MANUAL	C704	5KC49PN2521Y	*	D018	56B34D133	\$345	F1	21.3 / 10.6	11.91	2,18
	3600	115/208-230	143T	NONE	I101	143TCDR5303	*			\$342	S1	18.8/9.7-9.4	10.99	2,14,18
	1800	115/230	56	NONE	C1299	5KCR48WN0756Y	*			\$414	F1	13.4/6.7	12.45	ES,1,110
	1800	115/208-230	56H	MANUAL	G951	56C17D5308	*			\$414	F1	18.0/9.3-9.0	12.44	2,14,18
	1800	115/208-230	56H	NONE	C185	5KCR49SN0068	*	G939	56C17D5306	\$382	F1	18.2/9.1-9.1	11.90	ES,1,18
	1800	115/208-230	56H	AUTO	C186	5KCR49SN0068X	*	G950	56C17D5307	\$397	F1	18.2/9.1	11.90	ES,1,18
	1800	115/208-230	145T	NONE	C191	5KCR49SN0065	*	I111	145TCDR5326	\$388	S1	18.2/9.1-9.1	12.30	ES,1,18
	1200	115/230	184T	NONE	I1142	184TCDW7076	*	I142	184TCDR7076	\$668	S1	23.0/11.5	15.72	2,13,18
2	3600	115/230	56	NONE	C187	5KC48TN2169	*	G952	56B34D5321	\$397	F1	21.2 / 10.6	12.66	2,18
	3600	115/230	56	MANUAL	9035	5KCR48TN2650Y	*	D012	56B34D5318	\$432	F1	17.9/8.5	12.76	ES,1,17
	3600	115/230	56	MANUAL	C703	5KC49RN2520Y	*			\$542	F1	23.8/11.8	11.91	2,18
	3600	115/208-230	145T	NONE	I102	145TBDR5302	*			\$408	S1	19.2/10.5-9.6	11.49	1,18
	1800	115/208-230	56HZ	NONE	C193	5KCR49WN0270	*	I118	145TBDR5326	\$405	F1	22.0/10.9-11.0	14.33	ES,1,11,18
	1800	115/208-230	56HZ	AUTO	CG381	5KCR49WN0270T	*			\$520	F1	22.0/10.9-11.0	14.33	ES,1,11,18
	1800	115/208-230	145T	MANUAL	I127	145TBDR5337	*			\$497	S1	18.8/10.2-9.4	13.49	1,11,18
	1800	115/208-230	182T	NONE	I1112	182TCDW7026	*	I112	182TCDR7026	\$453	S1	23.0/12.3-11.5	13.19	2,13,18
	1200	115/208-230	213T	NONE	I143	213TCDW7076	*			\$830	S1	30.0/15.5-15.0	16.55	2,18
3	3600	230	56	MANUAL	9036	5KCR48UN2653Y	*	D013	56B34D5332	\$563	F1	14.5	12.64	ES,1,17
	3600	115/230	145T	NONE	C194	5KCR48TN8062	*			\$571	S1	29.4/14.7	13.13	ES,1,18
	3600	208/230	145T	NONE	I145	145TBDR5303	*			\$442	S1	13.5-12.5	11.99	1,7,17
	3600	115/208-230	182T	NONE	I103	182TCDR7001	*			\$509	S1	32.0/17.5-16.0	13.22	d,2,18
	3600	115/208-230	182T	NONE	I1103	182TCDW7001	*			\$509	S1	32.0/17.1-16.1	13.69	2,13,18
	1800	115/208-230	184T	NONE	I113	184TCDR7026	*			\$529	S1	33.0/17.5	15.22	d,2,18
	1800	115/208-230	184T	NONE	I1113	184TCDW7026	*			\$529	S1	33.5/17.4-16.8	14.21	2,13,18
	1200	230	215T	NONE	I144	215TBDW7079	*			\$1,143	S1	16.0	18.05	1,18
5	3600	230	56H	MANUAL	D017	56B34D5302	*			\$599	F1	20.0	13.94	1,5,18
	3600	208-230	184T	NONE	I104	184TCDR7001	*			\$684	S1	27.0-24.0	14.72	d,2,18
	3600	208-230	184T	NONE	I1104	184TBDW17008	*			\$684	S1	24.0-22.0	14.69	2,13,18
	1800	208-230	184T	NONE	I114	184TBDR7026	*			\$642	S1	23.5-21.0	15.72	d,DS,1,18
	1800	208-230	184T	NONE	I1114	184TBDW7026	*			\$642	S1	23.0-21.0	14.71	DS,1,13,18
	1800	208-230	213T	NONE	I117	213TCDW7026	*			\$874	S1	30.5-28.0	16.55	2,18
7 1/2	3600	208-230	184T	NONE	I1108	184TBDW7001	*			\$720	S1	34.0-31.0	16.69	1,13,18
	3600	208-230	213T	NONE	I105	213TCDW7001	*			\$974	S1	40.0-37.0	16.55	2,18
	1800	208-230	215T	NONE	I115	215TBDW7026	*			\$961	S1	37.2-34.5	18.05	1,18
10	3600	208-230	215T	NONE	I106	215TCDW17002	*			\$1,249	S1	51.0-46.0	18.05	2,18
	1800	208-230	215T	NONE	I116	215TBDW7028	*			\$1,237	S1	49.0-44.0	19.30	1,7,18


SINGLE PHASE

Extended Thru-Bolts, Split Phase - Steel endshields

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115	48Z	NONE	H901	5KH32DNA612	*	\$118	F1	5.1	9.83	9,18,28
	1800	115	48Z	AUTO	H902	5KH32DNA612X	*	\$123	F1	5.1	9.83	9,18,28
1/3	1800	115	48Z	NONE	H903	5KH32FNA611	*	\$122	F1	5.5	9.83	9,18,28
	1800	115	48Z	AUTO	H904	5KH32FNA611X	*	\$126	F1	5.5	9.83	9,18,28
1/2	1800	115	56Z	NONE	H905	5KH36JNA769	*	\$143	F1	8.1	10.89	10,18,28
	1800	115	56Z	AUTO	H906	5KH36JNA769X	*	\$148	F1	8.1	10.89	10,18,28
3/4	1800	115	56Z	NONE	H907	5KH37NNA768	*	\$175	F1	11.2	11.29	10,17
	1800	115	56Z	AUTO	H908	5KH37NNA768X	*	\$180	F1	11.2	11.29	10,17

Special Purpose, Single Phase

(1.0 Service Factor), Dripproof



Features:

- Ball bearings (unless otherwise noted)
- Heavy gauge steel constructions
- 1.0 Service Factor
- Economical split phase or capacitor start designs
- UL Recognized and CSA Certified


Rigid Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115	48	NONE	4351	5KH39QN9542	*	\$105	F1	5.7	8.94	d,3,4,7
	1800	115	48	NONE	S003	48S17D2089	*	\$105	F1	6.0	9.09	3,7
	1500	110/220	48	AUTO	H689	5KH35JN603X	*	\$215	F1	5.2/2.6	9.23	3,7,50
1/3	1800	115	48	AUTO	4380	5KH39QN9681X	*	\$151	F1	6.2	8.94	3,4,7
	1800	115	48	AUTO	S026	48S17D2113	*	\$122	F1	6.6	9.34	3,7
	1800	115	48	NONE	4368	5KH39QN9397	*	\$117	F1	6.2	8.94	3,4,7
	1800	115	48	NONE	S006	48S17D2090	*	\$117	F1	6.6	9.34	3
	1800	115	48	NONE	H229	5KH35HN9	*	\$191	F1	6.8	9.25	3,7
	1800	115/230	48	NONE	S010	48C17D2023	*	\$158	F1	7.0/3.5	9.34	2
	1800	115/230	48	MANUAL	S030	48C17D2027	*	\$189	F1	7.0/3.5	9.34	2
	1800	115/230	48	AUTO	S011	48C17D2024	*	\$166	F1	7.0/3.5	9.34	
	1800	230	48	NONE	4373	5KH39QN9543	*	\$165	F1	3.3	8.94	3,4,7
	1800	115	48Z	NONE	4376	5KH39QN9547	*	\$157	F1	6.2	10.36	3,4,7
	1800	115	56Z	NONE	4372	5KH39QN9546	*	\$161	F1	6.2	8.94	3,4,7
	1800	115	56Z	NONE	H676	5KH35GNA229	*	\$191	F1	6.2	9.57	3,7
	1800	115/230	56	MANUAL	CG095	5KC35JN27Y	*	\$226	F1	6.6/3.3	9.89	d,2
	1500	110/220	48	AUTO	H691	5KH36LN488X	*	\$230	F1	7.0/3.5	9.66	3,7
1/2	1800	115	48	NONE	H696	5KH36LNA504	*	\$227	F1	8.3	9.68	3,7
	1800	115	56	AUTO	9029	5KC49NN0221X	*	\$205	F1	8.7	11.14	2
	1800	115	56	AUTO	S027	56S17D2066	*	\$155	F1	9.2	10.22	3
	1800	115	56	NONE	H230	5KH39QN9091	*	\$149	F1	8.3	10.32	d,3,4,7
	1800	115	56	NONE	S022	56S17D2046	*	\$149	F1	9.2	10.22	3
	1800	115/230	56	NONE	S012	56C17D2098	*	\$195	F1	9.2/4.6	10.22	2
	1800	115/230	56	MANUAL	S033	56C17D2064	*	\$226	F1	9.2/4.6	10.22	2
	1800	115/230	56	AUTO	S013	56C17D2051	*	\$203	F1	9.2/4.6	10.22	2
	1800	115/230	56Z	NONE	CG393	5KC36MN20	*	\$273	F1	8.2/4.1	12.30	2
3/4	3600	115/230	48	NONE	CG111	5KC37LN91	*	\$389	F1	11.2/5.6	10.06	2,7
	1800	115/230	56	MANUAL	S036	56C17D2067	*	\$266	F1	10.4/5.2	11.97	2
	1800	115/230	56	AUTO	S015	56C17D2055	*	\$242	F1	10.4/5.2	11.97	2
	1800	115/230	56	NONE	S014	56C17D2054	*	\$233	F1	10.4/5.2	11.97	2
1	3600	115/230	56Z	NONE	C449	5KC37NN160	*	\$306	F1	13.4/6.7	12.60	2
	1800	115/230	56	MANUAL	S039	56C17D5320	*	\$345	F1	13.6/6.8	10.94	2
	1800	115/230	56	AUTO	S038	56C17D5343	*	\$321	F1	13.6/6.8	10.94	2
	1800	115/230	56	NONE	S037	56C17D5319	*	\$313	F1	13.6/6.8	10.94	2
1 1/2	3600	115/230	56	MANUAL	9034	5KC49NN2044Y	*	\$263	F1	19.0/9.5	11.14	2
2	3600	115/230	56	MANUAL	9035	5KCR48TN2650Y	*	\$432	F1	17/8.5	12.76	ES,1
3	3600	208-230	145T	NONE	I145	145TBDR5303	*	\$442	S1	13.5/12.5	12.49	1
5	3600	230	56H	MANUAL	9038	5KCR49ZN2151U	*	\$599	F1	21.0	15.04	ES,1

SINGLE PHASE

General Purpose, Single Phase

(NEMA Service Factor), Drip-proof



Features:

- Ball bearings (except as noted)
- Heavy gauge steel constructions
- Thermal protection, as noted
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- 48Y and 48YZ have 48/56 Fr mounting holes
- Service Factor, as noted
- UL Recognized and CSA Certified

Resilient Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES	
1/4	1800	115	48	AUTO	CG201	5KC35JN12X	*			\$209	F1	5.2	9.57	4,7,20	
	1800	115	48	NONE	C200	5KC35JN12	*			\$204	F1	5.2	9.57	4,7,20	
	1800	115/230	48	NONE	G1114	5KC35JN7	*	G114	48C17D2036	\$162	F1	5.2/2.6	9.57	4,7,20	
	1800	115/230	48	AUTO	G1115	5KC35JN7X	*	G115	48C17D2018	\$171	F1	5.2/2.6	9.57	4,7,20	
	1500	110/220	48	AUTO	C460	5KC36LN19X	*			\$263	F1	5.6/2.8	10.00	7,20,50	
1/3	3600	115/230	48	AUTO	C208	5KC35FN51X	*			\$222	F1	6.8/3.4	9.57	7,20	
	1800	100-120/200-240	56	AUTO	E254	5KCR46JN0086X	*			\$315	F1	4.0-3.8/2.0-1.9	10.77	ES,1,20,68	
	1800	115/208-230	48	NONE	C209	5KC36LN26	*			\$252	F1	6.0/3.2-3.0	10.00	7,20,68	
	1800	115/208-230	48	AUTO	C210	5KC36LN26X	*			\$266	F1	6.0/3.2-3.0	10.00	7,20,68	
	1800	115/230	56	AUTO	G135	56C17D2088	*			\$207	F1	6.4/3.2	10.22	20	
	1800	115/208-230	56	NONE	C215	5KC36LN1	*			\$273	F1	6.0/3.2-3.0	10.32	20,68	
	1800	115/208-230	56	AUTO	C216	5KC36LN1X	*	B210	56C17D2100	\$225	F1	6.0/3.2-3.0	10.32	20,68	
	1500	110/220	56	AUTO	C457	5KC37NN14T	*			\$319	F1	7.4/3.7	10.72	20,50	
	1200	115/230	56	NONE	C1258	5KC49PN6051	*			\$370	F1	8.6/4.3	11.38	20	
	1200	115/230	56	AUTO	C548	5KC49PN6051X	*			\$381	F1	8.6/4.3	11.38	20	
1/2	3600	115/208-230	48	AUTO	D1110	5KC39QN3220X	*	D110	48C34D2022	\$164	F1	8.2/3.9-4.1	11.00	7,19	
	1800	100-120/200-240	56	AUTO	E263	5KCR46MN0054X	*			\$377	F1	5.8-5.6/2.9-2.8	10.77	ES,1,19,68	
	1800	115/208-230	56	NONE	B1316	5KC49GN0001	*	B316	56C17D2071	\$242	F1	8.8/4.2-4.4	10.38	19	
	1800	115/208-230	56	AUTO	C1153	5KC49GN0022X	*			\$274	F1	8.6/4.1-4.3	10.38	d,19	
	1800	115/208-230	56	AUTO	B317	56C17D2072	*			\$280	F1	7.2/3.6	10.47	CF,19,31	
	1800	115/230	56	AUTO	CG223	5KC49GN0001X	*			\$294	F1	8.8/4.4	10.38	19	
	1800	115/230	56	AUTO	D111	56C17D2079	*			\$246	F1	7.2/3.6	10.72	19	
	1800	115/230	56	AUTO	G151	56C17D2025	*			\$246	F1	8.6/4.3	11.72	19	
	1200	115/230	56	NONE	C1264	5KC48UN6052	*			\$528	F1	9.4/4.7	12.76	19	
	1200	115/230	56	AUTO	C552	5KC48UN6052X	*			\$539	F1	9.4/4.7	12.76	19	
	3/4	3600	115/208-230	48	AUTO	C1154	5KC38NN413X	*			\$301	F1	10.0/4.9-5.0	11.00	7,19
		3600	115/208-230	56	AUTO	C1155	5KC38NN410X	*	D117	56C34D2095	\$213	F1	10.0/4.9-5.0	11.32	19
		1800	100-120/200-240	56	AUTO	EG272	5KCR49PN0098X	*			\$469	F1	9.0-8.8/4.5-4.4	11.37	ES,1,17,68
1800		115/208-230	56	NONE	G156	56B17D2012	*			\$303	F1	11.0/5.5-5.5	11.47	1,19	
1800		115/208-230	56	AUTO	C1156	5KC46LN0149X	*			\$330	F1	13.3/6.5-6.6	10.78	19	
1800		115/208-230	56	AUTO	B319	56C17D2074	*			\$340	F1	10.6/5.3-5.3	11.72	CF,19,31	
1800		115/208-230	56	NONE	CG230	5KC46LN0158	*			\$305	F1	13.2/6.2-6.6	10.78	19	
1800		115/208-230	56	NONE	B318	56C17D2073	*			\$315	F1	10.6/5.3-5.3	11.72	CF,19,31	
1800		115/208-230	56	AUTO	C138	5KC46JN0002X	*			\$329	F1	11.4/5.6-5.7	10.78	19	
1800		115/230	56	AUTO	D1113	5KC46LN0158X	*	D113	56C17D2080	\$304	F1	13.2/6.6	10.78	19	
1500		110/220	56	AUTO	C1187	5KC49NN0224X	*			\$433	F1	12.2/6.1	11.38	19,50	
1200	115/230	56	NONE	CG232	5KCR49WN6007	*			\$610	F1	12.6/6.3	13.96	1,18		
1	3600	115/208-230	56	AUTO	C1157	5KC39RN383X	*	K136	56C34D5314	\$266	F1	13.4/6.7-6.6	11.90	19	
	3600	115/208-230	56	AUTO	D118	56C34D2106	*			\$249	F1	12.0/6.2-6.0	12.22	18	
	1800	100-120/200-240	56H	AUTO	E281	5KCR48UN0105X	*			\$492	F1	11.8-11.4/5.9-5.7	12.65	ES,1,18,68	
	1800	115/208-230	56	AUTO	C1158	5KC49PN0164X	*	D114	56C17D5345	\$345	F1	14.7/7.2-7.4	11.38	18	
	1800	115/208-230	56	NONE	C235	5KC49PN0155	*	B310	56C17D5321	\$322	F1	13.6/6.7-6.8	11.38	5,18	
	1800	115/230	56	AUTO	CG236	5KC49PN0155X	*			\$391	F1	13.6/6.8	11.38	18	

Continued on next page.

General Purpose, Single Phase

(NEMA Service Factor), Dripproof

Resilient Base


HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1 1/2	3600	115/208-230	56H	AUTO	C1159	5KC49RN2152T	★			\$346	F1	19.6/9.8-9.8	12.01	d,18
	3600	115/208-230	56	AUTO	D115	56B34D2027	★			\$346	F1	13.4/7.4-6.7	11.72	1,18
	1800	115/208-230	56H	NONE	B336	56C17D5347	★			\$386	F1	18.0/9.3-9.	12.85	5,18,32
	1800	115/208-230	56H	AUTO	CG239	5KCR49SN0012X	★			\$459	F1	18.2/9.1	11.91	ES,1,5,18
	1800	115/208-230	56H	AUTO	C1160	5KCR49SN0150X	★	B330	56C17D5316	\$401	F1	16.4/8.4-8.2	11.90	ES,1,18
	1800	115/208-230	145T	NONE	I146	145TCDR5331	★			\$392	S1	18.0/9.3-9.	13.22	18,32
2	3600	115/208-230	56H	AUTO	K152	56B34D5320	★			\$421	F1	19.2/10.5-9.6	11.85	1,5,18
	3600	115/208-230	56H	AUTO	C1161	5KCR49RN2148T	★			\$422	F1	19.6/10.4-9.8	11.91	ES,1,5,110
	1800	115/208-230	56H	AUTO	C1162	5KCR49WN0291T	★	B352	56B17D5331	\$512	F1	22.0/10.9-11.0	13.96	ES,1,5,18
	1800	115/208-230	145T	NONE	I147	145TBDR5345	★			\$412	S1	21/11.3-10.5	14.22	1,18

Two Speed, Variable Torque

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/2-1/6	1800/1200	115	56	AUTO	C419	5KC49PN3027X	★	\$467	F1	8.2/3.9	11.38	19
3/4-1/4	1800/1200	115	56	AUTO	C474	5KCR49PN3011X	★	\$510	F1	9.0/6.4	11.48	ES,1,19
	1800/1200	115	56	NONE	C420	5KCR49PN3011	★	\$433	F1	9.0/6.4	11.48	ES,1,19
	1800/1200	208-230	56	AUTO	C486	5KCR49PN3012X	★	\$442	F1	4.3-4.4/3.1-3.2	11.48	ES,1,19
1 1/3	1800/1200	115	56	AUTO	C1478	5KCR49SN3009X	★	\$562	F1	10.8/7.4	12.01	ES,1,18
	1800/1200	115	56	NONE	C475	5KCR49SN3009	★	\$541	F1	10.8/7.4	12.01	ES,1,18
	1800/1200	208-230	56	NONE	C476	5KCR49SN3010	★	\$562	F1	5.3-5.4/3.6-3.7	12.01	ES,1,18
	1800/1200	208-230/190-220	56H	AUTO	C1479	5KCR48TN3084X	★	\$573	F1	5.3-5.4/3.6-3.7	12.54	ES,1,17

Special Purpose, Single Phase

(1.0 Service Factor), Dripproof



Features:

- Ball bearings (except as noted)
- Heavy gauge steel constructions
- 1.0 Service Factor
- Economical split phase or capacitor start designs, as noted
- 48Y and 48YZ have 48/56 Fr mounting holes
- UL Recognized and CSA Certified

Resilient Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115	48	AUTO	S103	48S17D2091		\$117	F1	5.7	9.06	3,7,31
	1800	115	48	NONE	4352	5KH39QN5542	★	\$111	F1	5.7	8.93	d,3,4,7
	1800	115	48	NONE	S102	48S17D2042	★	\$111	F1	5.7	9.06	3,7
	1800	115/230	48	AUTO	S119	48C17D2046	★	\$162	F1	6.2/3.1	9.06	2,7
	1800	115/230	48	NONE	S118	48C17D2045	★	\$153	F1	6.2/3.1	9.06	2,7
	1800	115	48	NONE	H675	5KH33FNA230	★	\$184	F1	5.0	9.19	3,7
	1800	115	48	AUTO	4301	5KH39QN5518X	★	\$117	F1	5.7	8.93	d,3,4,7
	1800	115	48Z	AUTO	S126	48S17D2104	★	\$117	F1	5.3	9.72	3,53
	1800	115	56Z	AUTO	4364	5KH39QN5541X	★	\$158	F1	5.7	9.19	3,4,7
	1800	115	56Z	NONE	4359	5KH39QN5523	★	\$154	F1	5.7	9.19	3,4,7
	1500	220	48	NONE	H645	5KH39QN810	★	\$209	F1	3.4	9.57	3,7,50
	1500	110/220	56Z	AUTO	HG690	5KH35JN602X	★	\$222	F1	5.2/2.6	9.51	3,7,50

Continued on next page.

SINGLE PHASE

Special Purpose, Single Phase

(1.0 Service Factor), Dripproof

Resilient Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/3	1800	115	48	NONE	4369	5KH39QN5508	★	\$130	F1	6.2	8.94	3,4,7
	1800	115	48	NONE	S106	48S17D2093	★	\$132	F1	6.5	9.31	3,7,31,CF
	1800	115/230	48	AUTO	C129	5KC35JN23X		\$171	F1	6.4/3.2	9.57	2,4,7
	1800	115/230	48	AUTO	S111	48C17D2029	★	\$171	F1	7.0/3.5	9.31	2,7
	1800	115/230	48	NONE	S110	48C17D2028	★	\$162	F1	7.0/3.5	9.31	2,7
	1800	115	48	AUTO	4310	5KH39QN5508X		\$128	F1	6.2	8.94	3,4,7
	1800	115	48Y	AUTO	S127	48S17D2105	★	\$128	F1	6.6	9.72	3,5,3
	1800	115	48	NONE	H674	5KH35JNA231	★	\$198	F1	6.6	9.57	3,7
	1800	115	56Z	NONE	4377	5KH39QN5524	★	\$168	F1	6.2	9.19	3,4,7
	1800	115	56Z	AUTO	4381	5KH39QN5528X	★	\$172	F1	6.2	9.19	3,4,7
	1800	115	56Z	AUTO	4776	5KH39QN5539T	★	\$172	F1	6.2	9.19	3,4,7,57
	1800	230	48	NONE	4371	5KH39QN5529	★	\$168	F1	3.3	8.94	3,4,7
	1800	230	48	AUTO	4311	5KH39QN5529X	★	\$172	F1	3.3	8.93	3,4,7
	1500	110/220	56Z	AUTO	HG692	5KH36LN489X	★	\$238	F1	7.0/3.5	9.94	3,5,0
	1500	220	56Z	NONE	H673	5KH33KN5594	★	\$226	F1	3.5	9.19	3,4,7,50
1/2	1800	115	48Z	AUTO	HG710	5KH33JNA511T		\$155	F1	7.9	9.93	3,9
	1800	115	48Z	AUTO	S128	48S17D2106	★	\$155	F1	9.2	10.22	3,5,3
	1800	115	56	NONE	4386	5KH39QN9218	★	\$153	F1	8.3	10.32	d,3
	1800	115	56	NONE	S120	56S17D2023	★	\$153	F1	9.2	10.22	3,3,1
	1800	115	56Z	AUTO	4778	5KH39QN9639T	★	\$238	F1	8.3	9.57	3,7
	1800	115/230	56	AUTO	C136	5KC36MN4X	★	\$207	F1	8.2/4.1	10.32	d,2
	1800	115/230	56Z	AUTO	S113	56C17D2099	★	\$207	F1	9.1/4.5	10.22	2
	1800	115/230	56	NONE	S112	56C17D2097	★	\$199	F1	9.1/4.5	10.22	2
	1800	115/230	48	AUTO	C133	5KC36MN27X	★	\$288	F1	8.2/4.1	10.00	2,7
	1800	230	56	AUTO	4602	5KH39QN9518X	★	\$257	F1	4.2	10.32	3
	1800	230	56	NONE	4387	5KH39QN9684	★	\$250	F1	4.2	10.32	3
	1500	110/220	56	AUTO	H693	5KH46JN0329X	★	\$265	F1	9.2/4.6	10.55	3
3/4	1800	115/230	56	NONE	S114	56C17D2060	★	\$237	F1	10.4/5.2	11.97	2
	1800	115	56	NONE	4422	5KH39QN9687	★	\$294	F1	11.2	10.72	3
	1800	115/230	56	AUTO	C1483	5KC46LN0254X		\$246	F1	13.2/6.6	10.78	2
	1800	115/230	56	AUTO	S115	56C17D2061	★	\$246	F1	10.4/5.2	11.97	2
1	1800	115/230	56	AUTO	C636	5KC49NN0019X	★	\$326	F1	14.4/7.2	11.38	d,2
	1800	115/230	56	AUTO	S117	56C17D5340	★	\$326	F1	13.6/6.8	11.35	2
	1800	115/230	56	NONE	S116	56C17D5339	★	\$317	F1	13.6/6.8	11.35	2

SINGLE PHASE

General Purpose, Single Phase

(NEMA Service Factor), Dripproof



Features:

- Ball bearings, mechanically locked on shaft end
- Heavy gauge steel constructions
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- Service Factor, as noted
- UL Recognized and CSA Certified

C-Face Footless

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115/208-230	56C	NONE	C1296	5KC35JN70	★	\$189	F1	5.2/2.7-2.6	9.61	d,20
	1800	115/208-230	56C	NONE	G212	56C17D2084	★	\$189	F1	5.0/2.3-2.5	10.69	20
	1800	115/208-230	56C	AUTO	C354	5KC35JN70X	★	\$248	F1	5.2/2.7-2.6	9.61	20
1/3	3600	115/208-230	56C	NONE	G216	56C34D2117	★	\$162	F1	4.4/2.2-2.2	10.19	20
	1800	100-120/200-240	56C	NONE	E251	5KCR46JN0084	★	\$365	F1	4.0-3.8/2.0-1.9	10.77	ES,1,20,68
	1800	115/208-230	56C	AUTO	C356	5KC36LN83X	★	\$287	F1	6.0/3.2-3.0	10.35	20,68
	1800	115/208-230	56C	NONE	C355	5KC36LN83	★	\$222	F1	6.0/3.2-3.0	10.35	d,20,68
	1800	115/208-230	56C	NONE	G230	56C17D2085	★	\$222	F1	6.4/3.0-3.2	10.69	20
1/2	3600	115/208-230	56C	NONE	G232	56C34D2108	★	\$179	F1	8.4/3.8-4.2	10.69	19
	1800	100-120/200-240	56C	NONE	E260	5KCR46MN0091	★	\$416	F1	5.8-5.6/2.9-2.8	10.77	ES,1,19,68
	1800	115/208-230	56C	NONE	C358	5KC49GN0009	★	\$261	F1	8.8/4.2-4.4	10.38	19
	1800	115/208-230	56C	NONE	G234	56C17D2044	★	\$261	F1	8.6/4.1-4.3	11.19	19
	1800	115/230	56C	AUTO	C359	5KC49GN0009X	★	\$326	F1	8.8/4.4	10.38	19
	1200	115/208-230	56C	NONE	G278	56C11D5304	★	\$417	F1	10.6/5.1-5.3	11.94	19
3/4	3600	115/208-230	56C	NONE	G238	56C34D2101	★	\$229	F1	9.6/4.4-4.8	10.94	19
	1800	100-120/200-240	56C	NONE	E269	5KCR49PN0096	★	\$451	F1	9.0-8.8/4.5-4.4	11.38	ES,1,19,68
	1800	115/230	56C	AUTO	CG362	5KC46LN0159X	★	\$392	F1	13.2/6.6	10.78	19
	1800	115/208-230	56C	NONE	CG361	5KC46LN0159	★	\$320	F1	13.2/6.2-6.6	10.78	d,17
	1800	115/208-230	56C	NONE	G250	56B17D2011	★	\$320	F1	11.0/5.5-5.5	11.72	1,19
1	3600	115/208-230	56C	NONE	G254	56B34D2031	★	\$263	F1	10.6/5.5-5.3	11.68	1,19
	1800	100-120/200-240	56C	NONE	E278	5KCR48UN0103	★	\$519	F1	11.8-11.4/5.9-5.7	12.65	ES,1,18,68
	1800	115/230	56C	AUTO	CG363	5KC49PN0163X	★	\$438	F1	13.6/6.8	11.38	18
	1800	115/208-230	56C	NONE	C1297	5KC49PN0163	★	\$343	F1	13.6/6.7-6.8	11.38	d,18
	1800	115/208-230	56C	NONE	G256	56C17D5310	★	\$343	F1	13.4/6.8-6.7	11.44	18
1 1/2	3600	115/208-230	56C	NONE	G258	56B34D2023	★	\$341	F1	14.2/7.7-7.1	11.68	1,18
	1800	115/208-230	56C	NONE	G270	56C17D5311	★	\$399	F1	18.0/9.3-9.0	12.44	18
2	3600	115/208-230	56C	NONE	G272	56B34D5319	★	\$418	F1	19.2/10.5-9.6	11.44	1,18
	1800	115/208-230	56C	NONE	G274	56B17D5303	★	\$487	F1	21.0/11.3-10.5	13.44	1,18
3	3600	115/208-230	182TC	NONE	C173	182TCDR8007	★	\$559	S1	32.0/17.5-16.0	13.96	18
	1800	115/230	184TC	NONE	C1174	184TCDW9627	★	\$546	S1	33.0/16.5	15.96	13,18

SINGLE PHASE

General Purpose, Single Phase

(NEMA Service Factor), Dripproof



Features:

- Ball bearings, mechanically locked on shaft end
- NEMA Service Factors
- Heavy gauge steel constructions
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- UL Recognized and CSA Certified

C-Face Footed (Rigid Base)

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1800	115/208-230	56C	AUTO	K234	56C17D2114				\$203	F1	5.0/2.3-2.5	10.30	
1/3	1800	115/208-230	56C	AUTO	K235	56C17D2115	*			\$236	F1	6.4/3.0-3.2	10.30	
	1800	100-120/200/240	56C	MANUAL	E250	5KCR46JN0083Y	*			\$283	F1	4.0-3.8/2.0-1.9	10.77	ES,1,68
	1800	100-120/200/240	56C	AUTO	E252	5KCR46JN0083X	*			\$236	F1	4.0-3.8/2.0-1.9	10.77	ES,1,68
1/2	1800	100-120/200-240	56C	AUTO	E261	5KCR46MN0090X	*	K236	56C17D2116	\$274	F1	5.8-5.6/2.9-2.8	10.77	ES,1,68
	1800	100-120/200-240	56C	MANUAL	E259	5KCR46MN0090Y	*			\$328	F1	5.8-5.6/2.9-2.8	10.77	ES,1,68
3/4	1800	100-120/200-240	56C	AUTO	E270	5KCR49PN0095X	*	K237	56B17D2015	\$333	F1	9.0-8.8/4.5-4.4	11.37	ES,1,68
	1800	100-120/200-240	56C	MANUAL	E268	5KCR49PN0095Y	*			\$379	F1	9.0-8.8/4.5-4.4	11.37	ES,1,68
1	1800	100-120/200-240	56C	MANUAL	EG277	5KCR48UN0102Y	*			\$439	F1	11.8-11.4/5.9-5.7	12.65	ES,1,68
2	3600	115/208-230	56C	MANUAL	C1269	5KC49SN2537Y	*			\$561	F1	15.6/8.8-7.8	11.34	
3	3600	208-230	56C	MANUAL	C1270	5KC49ZN2539Y	*			\$686	F1	13.0-12.0	12.84	

General Purpose, Single Phase

Totally Enclosed



Features:

- Ball bearings
- Heavy gauge steel constructions
- Economical split phase or capacitor start designs, as noted
- Service Factor, as noted
- UL Recognized and CSA Certified

Rigid Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/6	1800	115	48	NONE	H116	5KH32EN66	★			\$212	F1	4.0	9.92	3,17
	900	115/230	56	NONE	C248	5KC49PN3036	★			\$553	F1	5.6/2.8	12.43	2,17
1/4	1800	115	48	AUTO	HG121	5KH32FN3123X	★			\$233	F1	5.1	9.92	3,17
	1800	115	48	NONE	HG120	5KH32FN3123	★			\$223	F1	5.1	9.92	3,17
	1800	115/230	48	AUTO	C243	5KC32GN9X	★			\$275	F1	5.4/2.7	10.00	2,17
	1800	115/230	48	NONE	C242	5KC32GN9	★			\$263	F1	5.4/2.7	10.00	2,17
	1800	230	48	AUTO	H243	5KH32GN68X	★			\$254	F1	2.7	9.92	3,17
	1500	110/220	48	NONE	C462	5KC33KN19	★			\$304	F1	5.4/2.7	10.17	2,17,50
	1800	115/208-230	56	MANUAL	G314	56C17F2052	★			\$220	F1	4.2/2.1-2.1	10.22	2,18
	1800	115/230	56	AUTO	CG251	5KC32GN19X	★			\$286	F1	5.4/2.7	10.38	2,17
	1800	115/230	56	NONE	G1312	5KC32GN19	★	G312	56C17F2054	\$205	F1	5.4/2.7	10.38	2,17
	1200	115/230	56	NONE	G1316	5KC49MN6061	★	G316	56C11F5300	\$311	F1	6.2/3.1	11.43	2,17
1/3	3600	115	48	AUTO	HG124	5KH33FN85X	★			\$243	F1	6.4	10.17	3,17
	3600	115	48	NONE	HG123	5KH33FN85	★			\$236	F1	6.4	10.17	3,17
	1800	115/230	56	AUTO	G1331	5KC35MN43X	★	G331	56C17F2048	\$239	F1	6.0/3.0	10.93	2,17
	1800	115/208-230	56	MANUAL	G332	56C17F2049	★			\$253	F1	6.0/3.0-3.0	10.47	2,18
	1800	100-120/200-400	56	NONE	E258	5KCR46JN0089	★			\$367	F1	4.0-3.8/2.0-1.9	11.83	ES,1,17,20,68
	1800	115/230	56	NONE	G1330	5KC35MN43	★	G330	56C17F2040	\$229	F1	6.0/3.0	10.93	2,17
	1200	115/230	56	NONE	C1333	5KC49PN6062	★	G333	56C11F5301	\$350	F1	8.6/4.3	12.43	2,17
1/2	3600	115/208-230	56	MANUAL	G393	56C34F5307	★			\$213	F1	8.4/4.0-4.2	11.82	2,14,18
	3600	115/230	56	MANUAL	C664	5KC36LN4003Y	★			\$213	F1	8.0/4.0	11.36	17,82
	3600	115/208-230	56	NONE	K339	56C34F5327	★			\$199	F1	8.4/4.0-4.2	11.82	2,14,18
	1800	100-120/200-240	56	NONE	E267	5KCR46MN0094	★			\$417	F1	5.8-5.6/2.9-2.8	11.83	ES,1,17,19,68
	1800	115/230	56	AUTO	C262	5KC42GN0014X	★	G338	56C17F2050	\$274	F1	8.6/4.3	11.00	2,17
	1800	115/208-230	56	MANUAL	G339	56C17F2051	★			\$291	F1	8.0/4.0-4.0	11.22	2,18
	1800	115/208-230	56	MANUAL	C661	5KC46GN0569Y	★			\$291	F1	9.0/4.5-4.5	11.83	18,82
	1800	115/208-230	56	NONE	C261	5KC42GN0014	★	G337	56C17F2041	\$258	F1	8.6/4.1-4.3	11.00	2,17
	1800	115/230	56	NONE	CG260	5KC37RN35	★			\$338	F1	8.8/4.4	11.38	2,17
	1200	115/230	56	NONE	C264	5KC49UN6065	★	G350	56B11F5300	\$443	F1	9.4/4.7	12.96	2,17
3/4	3600	115/208-230	56	MANUAL	G379	56C34F5309	★			\$259	F1	10.6/5.3-5.3	12.32	2,14,18
	3600	115/208-230	56	NONE	G352	56C34F5308	★			\$243	F1	10.6/5.3-5.3	12.32	2,14,18
	1800	100-120/200-240	56	NONE	EG276	5KCR49PN0101	★			\$465	F1	9.0-8.8/4.5-4.4	12.43	ES,7,19,68
	1800	115/230	56	AUTO	C269	5KC46PN0015X	★	G355	56C17F5307	\$336	F1	11.0/5.5	11.83	2,17
	1800	115/208-230	56	MANUAL	G356	56C17F5308	★			\$357	F1	11.0/5.4-5.5	12.32	2,14,18
	1800	115/208-230	56	NONE	C268	5KC46PN0015	★	G354	56C17F5306	\$318	F1	11.0/5.4-5.5	11.83	2,17
	1200	115/230	56	NONE	C271	5KCR48WN6066	★	G357	56B11F5301	\$529	F1	10.6/5.3	13.82	ES,1,17
	1200	115/208-230	143T	NONE	I707	143TBFR5376	★			\$553	S1	11.4/5.8-5.7	13.87	1,14,18

SINGLE PHASE

General Purpose, Single Phase

Totally Enclosed

Rigid Base

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1	3600	115/208-230	56	NONE	G359	56C34F5310	*			\$279	F1	12.4/6.7-6.2	12.32	2,14,18
	3600	115/230	56	AUTO	C273	5KC49NN2130X	*			\$293	F1	13.0/6.5	12.43	2,17
	3600	115/230	56	MANUAL	C663	5KC49NN2419Y	*			\$293	F1	13.2/6.6	12.43	18,82
	3600	115/208-230	56	MANUAL	G390	56C34F5311	*			\$293	F1	12.4/6.7-6.2	12.32	2,14,18
	3600	115/230	56	MANUAL	C274	5KC49NN2130Y	*			\$293	F1	13.0/6.5	12.43	2,17
	1800	115/230	56	MANUAL	C660	5KC49TN0568Y	*			\$374	F1	13.2/6.6	12.96	17,82
	1800	115/230	56	NONE	C275	5KC49TN0034	*	G371	56C17F5309	\$358	F1	13.2/6.6	12.96	2,17
	1800	100-120/200-240	56	NONE	E285	5KCR49UN0108	*			\$534	F1	11.8-11.4/5.9-5.7	12.96	ES,1,68
	1800	115/208-230	56	MANUAL	G373	56C17F5311	*			\$374	F1	13.4/6.8-6.7	12.82	2,14,18
	1800	115/230	56	AUTO	C276	5KC49TN0034X	*	G372	56C17F5310	\$367	F1	13.2/6.6	12.96	2,17
1800	115/230	143T	NONE	C295	5KC49TN0033	*	I210	143TCFR5326	\$374	S1	13.2/6.6	13.33	2,17	
1 1/2	3600	115/208-230	56H	MANUAL	G391	56B34F5321	*			\$384	F1	14.2/7.7-7.1	12.82	1,5,14,18
	3600	115/230	56	MANUAL	C662	5KC49SN2418U	*			\$384	F1	16.4/8.2	12.96	17,82
	3600	115/208-230	56H	NONE	G374	56B34F5320	*			\$357	F1	14.2/7.7-7.1	12.82	1,5,14
	3600	115/208-230	143T	NONE	I220	143TBFR5301	*			\$397	S1	14.2/7.7-7.1	12.87	1,14,18
	1800	115/208-230	56	MANUAL	C659	5KCR48WN0566Y	*			\$429	F1	14.5/7.1-7.3	13.82	18,82
	1800	115/208-230	56H	MANUAL	G378	56B17F5302	*			\$429	F1	15.2/8.2-7.6	13.82	1,5,14,18
	1800	115/208-230	56H	NONE	G1376	5KCR48WN0273	*	G376	56B17F5300	\$408	F1	14.5/7.1-7.3	13.82	ES,1,5,17
	1800	115/208-230	56H	AUTO	G1377	5KCR48WN0273X	*	G377	56B17F5301	\$422	F1	14.5/7.1-7.3	13.82	ES,1,5,17
	1800	115/208-230	145T	MANUAL	I201	145TBFR5327	*			\$474	S1	15.2/8.2-7.6	13.87	1,14,18
	1800	115/208-230	145T	NONE	C297	5KCR48WN0292	*	I211	145TBFR5326	\$421	S1	14.5/7.1-7.3	14.07	1,17
2	3600	115/230	56	MANUAL	G1392	5KCR49TN2139U	*	G392	56B34F5323	\$434	F1	17.8/8.9	14.27	ES,1,17
	3600	115/208-230	56H	NONE	K350	56B34F5322	*			\$418	F1	18.0/10.0-9.0	13.32	1,5,14,18
	3600	115/208-230	145T	NONE	I221	145TBFR5303	*			\$434	S1	18.0/10.0-9.0	13.37	1,14,18
	1800	115/230	145T	NONE	I700	145TBFR5334	*			\$530	S1	18.8/9.4	14.87	1,14,18
	1800	115/208-230	182T	NONE	I212	182TBFR5326	*			\$573	S1	20.0/10.8-10.0	15.65	F,1,18
3	3600	115/208-230	182T	NONE	I206	182TBFR5301	*			\$668	S1	24.6/13.9-12.3	15.81	1,17
	3600	208-230	145T	NONE	I204	145TBFR5301	*			\$591	S1	13.1-11.8	14.87	1,14,18
	3600	208-230	145T	MANUAL	I205	145TBFR5302	*			\$636	S1	13.1-11.8	14.87	1,14,18
	1800	115/208-230	184T	NONE	I213	184TCFR7726	*			\$684	S1	34.0/17.5-17.0	17.86	d,2,14,17
	1800	115/208-230	184T	NONE	I1213	184TBFW17044	*			\$684	S1	28.4/14.8-14.2	14.96	1,13,14,17
5	3600	208-230	184T	NONE	I223	184TBFR7701	*			\$853	S1	25.1-22.4	17.36	d,1,14,17
	3600	208-230	184T	NONE	I1223	184TBFW7701	*			\$853	S1	22.0-19.8	16.49	1,13,14,17
	1800	208-230	184T	NONE	I214	184TBFR7726	*			\$842	S1	22.8-20.2	18.06	d,1,14,17
	1800	208-230	184T	NONE	I1214	184TBFW7726	*			\$842	S1	21.5-19.5	17.46	1,13,14,17
	1800	208-230	213T	NONE	I216	213TBFW7026	*			\$908	S1	24.5-22.0	18.73	1,14,17
7 1/2	3600	208-230	213T	NONE	I224	213TBFW7001	*			\$1,145	S1	36.0-32.0	20.23	1,14,17
	1800	208-230	215T	NONE	I215	215TBFW7026	*			\$1,118	S1	35.0-30.0	21.48	1,14,17
10	3600	208-230	215T	NONE	I225	215TBFW7001	*			\$1,395	S1	44.0-41.5	20.23	1,14,17
	1800	230	215T	NONE	I217	215TBFW7027	*			\$1,434	S1	41.5	21.48	1,14,17

SINGLE PHASE

General Purpose, Single Phase

Totally Enclosed



Features:

- Ball bearings, mechanically locked on shaft end
- Heavy gauge steel constructions
- Suitable for horizontal or vertical mounting
- Economical split phase or capacitor start designs, as noted
- Will accept brake kits, see Accessory section (except as noted)
- Service Factor, as noted
- UL Recognized and CSA Certified

C-Face Footless

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/6	1800	115	56C	NONE	H244	5KH32EN124	*			\$259	F1	4.0	10.30	3,18
1/4	1800	115/230	56C	NONE	G1511	5KC32GN25	*	G511	56C17T2002	\$216	F1	5.4/2.7	10.30	2,17,24
1/3	3600	115/230	56C	NONE	C1419	5KC33FN31	*	G534	56C34T2004	\$192	F1	5.6/2.8	10.19	18,24
	1800	115/230	56C	NONE	E256	5KCR46JN0088	*			\$390	F1	3.8/1.9	11.84	ES,1,20,24,68
	1800	115/230	56C	NONE	G1513	5KC35MN73	*	G513	56C17F2042	\$249	F1	6.0/3.0	10.93	2,18
1/2	3600	115/208-230	56C	NONE	G514	56C34F5322	*			\$209	F1	8.4/4.0-4.2	11.82	2,18
	3600	115/230	56C	AUTO	C349	5KC36LN166X	*			\$298	F1	7.4/3.7	11.36	2,18
	1800	115/230	56C	NONE	E265	5KCR46MN0093	*			\$438	F1	5.6/2.8	11.84	ES,1,19,68
	1800	115/230	56C	AUTO	C446	5KC42GN0018X	*			\$351	F1	8.6/4.3	11.01	2,18
	1800	115/230	56C	NONE	G1515	5KC42GN0018	*	G515	56C17F2043	\$287	F1	8.6/4.3	11.01	2,18
	1200	115/230	56C	NONE	C1404	5KC49UN6067	*			\$602	F1	9.4/4.7	12.93	2,18
	1200	115/230	56C	NONE	C1422	5KC48UN6072	*			\$564	F1	9.4/4.7	12.61	2,19
	3/4	3600	115/208-230	56C	NONE	G516	56C34F5323	*			\$255	F1	10.6/5.3-5.3	12.32
1800		115/230	56C	NONE	E274	5KCR49PN0100	*			\$484	F1	8.8/4.4	12.44	ES,1,19,68
1800		115/230	56C	NONE	G1517	5KC46PN0032	*	G517	56C17F5314	\$345	F1	11.0/5.5	11.84	2,17
1	3600	115/208-230	56C	NONE	G518	56C34F5324	*			\$289	F1	12.4/6.7-6.2	12.32	2,18
	3600	115/230	56C	AUTO	C351	5KC49NN2133X	*			\$381	F1	13.0/6.5	12.44	2,18
	1800	115/230	56C	NONE	EG283	5KCR49UN0107	*			\$555	F1	11.4/5.7	12.97	ES,1,18,68
	1800	115/230	56C	NONE	G1519	5KC49TN0035	*	G519	56C17F5315	\$368	F1	13.2/6.6	12.97	2,17
1 1/2	3600	115/230	56C	NONE	C1424	5KC49SN2158	*	G530	56B34F5329	\$367	F1	16.4/8.2	12.93	2,17,111
	3600	115/230	56C	AUTO	C855	5KC49SN2156X	*			\$466	F1	16.4/8.2	12.93	2,17
	1800	115/208-230	56C	NONE	G1531	5KCR48WN0294	*	G531	56B17F5303	\$425	F1	14.5/7.1-7.3	13.69	ES,1,18
2	3600	115/208-230	56C	NONE	G533	56B34F5319	*			\$445	F1	18.0/10.0-9.0	13.32	1,18
	3600	115/230	56C	AUTO	C466	5KCR49TN2155T	*			\$571	F1	17.8/8.9	14.28	1,17

SINGLE PHASE

General Purpose, Single Phase

Totally Enclosed



Features:

- Ball bearings, mechanically locked on shaft end
- Heavy gauge steel constructions
- Suitable for horizontal or vertical mounting
- Economical split phase or capacitor start designs, as noted
- Will accept brake kits, see Accessory section (except as noted)
- Service Factor, as noted
- UL Recognized and CSA Certified

C-Face Footed (Rigid Base)

HP	RPM	VOLTS	FRAME	OVER LOAD	CAT. NO.	MODEL NO.	STOCK	FORMER CAT NO	FORMER MODEL NO.	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1200	115/230	56C	NONE	C1423	5KC49MN6063	★			\$333	F2	6.2/3.1	11.40	d
1/3	1800	115/230	56C	AUTO	E257	5KCR46JN0087X	★			\$406	F1	3.8/1.9	11.84	ES,1,20,68
	1800	115/230	56C	MANUAL	E255	5KCR46JN0087Y	★			\$409	F1	3.8/1.9	11.84	ES,1,20,68
	1800	115/208-230	56C	MANUAL	F131	56C17F5358	★			\$325	F1	6.6/3.1-3.3	11.82	2,18
	1800	115/230	56C	NONE	C1405	5KC35MN145	★	G550	56C17F2044	\$253	F1	6.0/3.0	10.93	2,18
1/2	3600	115/208-230	56C	NONE	C1420	5KC36LN144	★	G559	56C34F5329	\$213	F1	7.4/3.7	11.36	2,17
	3600	115/230	56C	NONE	C444	5KC36LN144X	★			\$220	F2	7.4/3.7	11.36	d
	1800	115/230	56C	MANUAL	E264	5KCR46MN0055Y	★			\$453	F1	5.6/2.8	11.84	ES,1,19,68
	1800	115/230	56C	AUTO	E266	5KCR46MN0055X	★			\$442	F1	5.6/2.8	11.84	ES,1,19,68
	1800	115/208-230	56C	MANUAL	F132	56C17F5912	★			\$363	F1	8.8/4.2-4.4	11.82	2,18
	1800	115/230	56C	NONE	C375	5KC42GN0066	★	G551	56C17F2045	\$291	F1	8.6/4.3	11.01	2,18
3/4	1800	115/230	56C	MANUAL	EG273	5KCR49PN0099Y	★			\$505	F1	8.8/4.4	12.44	ES,1,19,68
	1800	115/230	56C	AUTO	E275	5KCR49PN0099X	★			\$496	F1	8.8/4.4	12.44	ES,1,19,68
	1800	115/208-230	56C	MANUAL	F133	56C17F5913	★			\$422	F1	11/5.4-5.5	12.32	2,18
	1800	115/230	56C	NONE	C1425	5KC49PN0283	★	G552	56C17F5318	\$350	F1	11.0/5.5	12.40	2,17
	1200	115/230	56C	NONE	C1412	5KCR49WN6078	★			\$566	F2	12.6/6.3	13.81	d,ES,1
1	3600	115/230	56C	AUTO	C445	5KC49NN2132X	★			\$300	F2	13.0/6.5	12.44	d
	1800	115/230	56C	MANUAL	EG282	5KCR49UN0106Y	★			\$575	F1	11.4/5.7	12.97	ES,1,19,68
	1800	115/230	56C	AUTO	EG284	5KCR49UN0106X	★			\$571	F1	11.4/5.7	12.97	ES,1,19,68
	1800	115/230	56C	NONE	C376	5KC49TN0067	★	G553	56C17F5319	\$374	F1	13.2/6.6	12.97	2,17
	1800	115/208-230	56C	MANUAL	F134	56C17F5914	★			\$454	F1	13.4/6.8-6.7	12.82	2,18
1 1/2	3600	115/208-230	56C	NONE	K631	56B34F5324				\$371	F1	14.2/7.7-7.1	12.82	1,18
	1800	115/208-230	56HC	MANUAL	F135	56B17F5584	★			\$545	F1	15.2/8.2-7.6	13.82	1,5,18
	1800	115/208-230	145TC	NONE	C281	145TBFR5337				\$530	S1	15.2/8.2-7.6	13.87	1,18
2	3600	115/208-230	145TC	NONE	C282	145TBFR5305				\$591	S1	16.6/9.1-8.3	13.37	1,18
	1800	115/230	56HC	MANUAL	K319	56B17F5319	★			\$559	F1	18.8/9.4	14.82	1,5,18
3	3600	208-230	145TC	NONE	C284	145TBFR5306				\$634	S1	13.1-11.8	14.87	1,18
	1800	230	184TC	MANUAL	I314	184TBFR7041	★			\$838	S1	13.7	17.61	d,1,18
	1800	230	184TC	MANUAL	I1314	184TBFW7041	★			\$838	S1	13.7	17.61	1,13,18
5	1800	230	184TC	MANUAL	I315	184TBFR7034	★			\$1,000	S1	21	18.72	d,1,18
	1800	230	184TC	MANUAL	I1315	184TBFW7034	★			\$1,000	S1	21	18.72	1,13,18

SINGLE PHASE

General Purpose, Single Phase

Totally Enclosed,



Features:

- Double sealed ball bearings, mechanically locked on shaft end
- Heavy gauge steel constructions
- Bolt-on, removable rigid base
- Suitable for horizontal or vertical mounting
- Capacitor start design for high starting torque
- Capacitor start/capacitor run design for higher efficiency, as noted
- 1.15 Service Factor (except as noted)
- Will accept brake kits, see Accessory section (except as noted)
- Will accept drip cover kits, see Accessories section
- UL Recognized and CSA Certified

C-Face Footed (Removable Base)

HP	RPM	VOLTS	FOUR-N ONE	FRAME LOAD	OVER NO.	CAT. NO.	MODEL	STOCK	LIST PRICE	MULT. SYMB.	F.L. AMPS	"C" DIM.	FOOT NOTES
1/4	1200	115/208-230	◆	56C	NONE	G577	56C11F5302	★	\$333	F2	6.8/3.1-3.4	11.82	
1/3	1800	115/208-230	◆	56C	NONE	G570	56C17F5320	★	\$259	F2	6.6/3.1-3.3	11.82	68
	1200	115/208-230	◆	56C	NONE	G576	56C11F5303	★	\$371	F2	7.8/3.6-3.9	12.32	
1/2	3600	115/208-230	◆	56C	NONE	D311	56C34F5301	★	\$220	F2	8.4/4.0-4.2	11.82	
	1800	115/208-230	◆	56C	NONE	G571	56C17F5321	★	\$297	F2	8.8/4.2-4.4	11.82	68
	1200	115/208-230	◆	56C	NONE	G578	56B11F5303	★	\$453	F2	9.6/4.7-4.8	13.32	1.68
3/4	3600	115/208-230	◆	56C	NONE	D312	56C34F5302	★	\$266	F2	10.6/5.3-5.3	12.32	
	1800	115/208-230	◆	56C	NONE	G572	56C17F5322	★	\$357	F2	11.0/5.4-5.5	12.32	68
	1200	115/208-230	◆	56C	NONE	G579	56B11F5302	★	\$566	F2	11.4/5.8-5.7	13.82	1
1	3600	115/208-230	◆	56C	NONE	D313	56C34F5303	★	\$300	F2	11.2/5.7-5.6	12.32	
	1800	115/208-230	◆	56HC	NONE	G573	56C17F5323	★	\$380	F2	13.4/6.8-6.7	12.82	5,68
1 1/2	3600	115/208-230	◆	56C	NONE	D314	56B34F5326	★	\$378	F2	14.2/7.7-7.1	12.82	1
	1800	115/208-230	◆	56HC	NONE	G574	56B17F5305	★	\$436	F2	15.2/8.2-7.6	13.82	1,5,68
2	3600	115/208-230	◆	56HC	NONE	D315	56B34F5327	★	\$455	F2	16.6/9.1-8.3	13.82	1,5
	1800	115/208-230	◆	56HC	NONE	G575	56B17F5306	★	\$546	F2	20.0/10.8-10.0	14.82	1,5,17
3	3600	208-230	◆	56HC	NONE	D316	56B34F5328	★	\$608	F2	13.1-11.8	14.82	1,5